

# evolutionDrive Plus<sup>+</sup>



- ✓ installation depth 152 mm
- ✓ glazing with packages up to 49 mm wide
- ✓ maximum dimensions of the fix sash (LxH) – 4000 x 2480 mm
- ✓ maximum dimensions of the movable sash (HxL) – 2000 x 2400 mm
- ✓ maximum sash weight – 170 kg

**5**

Chambers

**1**

Guiding Rail

**evolutionDrive Plus+ is a PVC sliding system** designed to retain all the most important advantages of sliding solutions while bringing thermal insulation closer to the level typical for windows and doors with turn-only fittings.

evolutionDrive Plus+ uses special fittings that provide increased pressure of the sash to the frame around the entire circumference. **Together with a system of three gaskets and a complete double seal around the perimeter, they ensure effective sealing, which translates into low thermal transmittance** of the entire structure.

The fittings allow you to set the handle in the closed position at any sash position. **In this way, you can improve ventilation by creating a small gap** or even create a passage for pets.

The system uses **closed reinforcements made of galvanized steel with a thickness of 1.5 and 2.5 mm, thus increasing the static parameters of the structure** and increasing its durability. Thanks to this, the maximum sash area can be up to 4.8 m<sup>2</sup>.

**evolutionDrive Plus+ is manufactured by taking into account solutions that facilitate its installation.** The need for servicing has also been reduced to a minimum, mainly by using carriages with linear ball bearings with a hardened axle. Moreover, the use of a smooth V-Super weld gives it an aesthetic appearance.

