

# Ideal 7000 NL



- ✓ profile with a construction depth of 4-3/4" (120 mm)
- ✓ overall glazing thickness up to 2-1/16" (52 mm) | standard IGU 1-7/8" (24 mm)
- ✓ two anti-burglary locking points per sash
- ✓ closed steel reinforcement in frame as standard
- ✓ available colors of core: white, cream, anthracite

**0,27**

U-Factor | simulated with double glazing\*

**2**

Gaskets

**5**

Chambers

IDEAL is a popular warm window joinery system. Millions of homes around the world use various setups based on this solution. Users appreciate it because of its excellent thermal and acoustic insulation and outstanding price-to-quality ratio.

The IDEAL 7000 NL variation was designed for the Dutch market. Its profiles can be welded at an angle of 45° using aesthetic V-super and V-perfect techniques or at 90° using the HFL technology. This method of welding makes the windows look like wooden structures.

Clients can order windows in solid colours or with wood-like veneers. Veneers can be used on the inside and outside of the window. Thanks to the fact that they can be selected independently, the IDEAL 7000 NL windows will easily match any facade and interior.

\* The above U-factor is a general achievable value for this window system. The detailed value can be provided with the selected IGU and product type.

PVC

ALUPLAST

IDEAL 7000 NL

ID 7000 NL

WINDOWS